



Phone (800)-558-4388
Fax (262)-820-1070

[Request for Quote](#)

Heyco » Wire Positioning Devices » Cable Tie Mounting Platforms



Material: 6/6 Nylon **RoHS Compliant**

Certifications:

File E54523

Flammability Rating: 94V-2

Material Temperature Index: 85°C (185°F)

- Multiple sizes anchor cable ties securely.
- Three styles:
 - Adhesive backed (may also be screw mounted, except for MP-4A's)
 - Screw Mount
 - Push Mount
- Rubber based adhesive will hold in temperatures up to 52°C (125°F).
- Apply to a clean, dry surface.

Heyco® Cable Tie Mounting Platforms

Wire Tie Insertion Points	Mounting Style	Part Number	Description	Screw Size		Part Dimensions		Use with Wire Ties of Maximum Tensile Strength	
				in.	mm.	in.	mm.	lbs.	N.
4	Adhesive	3594	MP-4A-S	–	–	.750 x .750	19,1 x 19,1	40	178
2	Adhesive	3590	MP-2A	8	4,1	1.00 x 1.00	25,4 x 25,4	50	222
4	Adhesive	3593	MP-4A	8	3,5	1.12 x 1.12	28,4 x 28,4	50	222
2	Push Mount	3762	MP-PM-250	Mounts into a .250"(6,4 mm) Diameter Hole		.313 x .563	7,9 x 14,3	50	222
2	Screw	3759	MP-S-68	8	4,1	.375 x .625	9,5 x 15,9	50	222
2	Screw	3753	MP-S-10	10	5,1	.625 x .875	15,9 x 22,2	120	534
2	Screw	3756	MP-S-250	1/4	6,4	.625 x .875	15,9 x 22,2	120	534
2	Screw	3756	MP LPM-56	5-6	–	.400 x .310	10,2 x 7,9	18	80
2	Screw	3757	MP LPM-68	6-8	–	.750 x .500	19,1 x 12,7	50	222

